

Li-Polymer Battery

Drawing:



Item 项目		Rating 参数	Note 标注
1.1 Capacity 容量	Typical 标称容量	550 mAh	Temperature/温度: 25±5℃
	Minimum 最小容量	540 mAh	Charge/充电: 0.2C Discharge/放电: 0.2C
1.2 Nominal Voltage 标称电压		Average 3.8V	
1.3 AC Impedance Resistance 内阻		≤90mΩ	Cell
		≤180mΩ	Battery Pack
1.4 Discharge Cut-off Voltage 放电截止电压		3.0V	
1.5 Charge voltage 充电限制电压		4.35V	Cut-off current≤11mA
1.6 Max Charge Continuous 最大充电电流		550mA	+10~+45℃
1.7 Max Discharge Continuous 最大连续放电		550mA	+10~+45℃
1.8 Weight / 重量		Approx 12.0g	
1.9 Cycle Life 循环寿命		500 cycles	Capacity ≥80%
1.10 Shipping Voltage / 出厂电压		3.8-4.1V	
1.11 Operating Temperature 工作温度	Charge 充电	0~+45℃	Max Charge:550mA
	Discharge 放电	-20~+60℃	Max Discharge:550mA
Model Name: <u>602133-550mAh</u>			
Battery size: T6.0*W21.5*L35mm		Wire (L1) 50±3mm (UL3302 28#)	Connector: SHR-02V-S-B
Overcharge detection voltage 过充电检测电压:		4.405--4.445V	
Overdischarge detection voltage 过放电检测电压:		2.450--2.550V	
Overcurrent protection current 过电流保护电流:		2~5A	
NTC:		MOS: PT8205	
IC: DS3001-DAG			