
Li-Polymer Battery

LithoTop

Your One-Stop Custom Battery Solution Partner

Drawing:



Item 项目		Rating 参数	Note 标注
1.1 Capacity 容量	Typical 标称容量	120 mAh	Temperature/温度：25±5℃ Charge/充电：0.2C Discharge/放电：0.2C
	Minimum 最小容量	110 mAh	
1.2 Nominal Voltage 标称电压		Average 3.7V	
1.3 AC Impedance Resistance 内阻		≤220mΩ	Cell
		≤310mΩ	Battery Pack
1.4 Discharge Cut-off Voltage 放电截止电压		3.0V	
1.5 Charge voltage 充电限制电压		4.2V	Cut-off current≤2.4mA
1.6 Max Charge Continuous 最大充电电流		120mA	+10~+45℃
1.7 Max Discharge Continuous 最大连续放电		120mA	+10~+45℃
1.8 Weight / 重量		Approx 30g	
1.9 Cycle Life 循环寿命		300 cycles	Capacity ≥80%
1.10 Shipping Voltage / 出厂电压		3.7-4.05V	
1.11 Operating Temperature 工作温度	Charge 充电	0~+45℃	Max Charge:120mA
	Discharge 放电	-20~+60℃	Max Discharge:120mA

Model Name: 501225-120mAh

Battery size: T5.1*W12.5*L28mm	Wire (L1) 20±3mm (UL3302 26#)	Connector: JST-PHR-3P
Overcharge detection voltage 过充电检测电压: 4.255--4.305V		
Overdischarge detection voltage 过放电检测电压: 2.950--3.050V		
Overcurrent protection current 过电流保护电流: 1.2~2.5A		
NTC: 10KΩ/B=3435K	MOS: PT8205	
IC: DM5268-G3J		

Rm. 4A, Huaqiang Chuangyi Industry Park, Biyan Area, Guangming, Shenzhen, China.
Tel: +86-755-21061176 https://lithotop .com sales@lithotop.com